Canon

Multimedia Projectors/Visualizer



www.canonprojectors.com

LV-7575



19.2 LBS. (8.7KG)

FEATURES

Please see page 3 for lens options.

- Native XGA Resolution (1024 x 768)
- 5500 ANSI Lumens (Normal Mode), 90% Uniformity
- 800:1 Contrast Ratio
- Lens: f=48.4 to 62.8mm, F1.8 to 2.1, 1.3x Zoom
- Lens Shifting: 1:1 to 10:0
- Throw Distance: 3.7 to 29.1 ft. (1.4 to 14.7m)
- Projected Image Size: 31 to 400 in.
- Throw Ratio: 1.77 to 2.33:1 (D:W)
- Digital Keystone Correction (±35 degrees Vertical, ±15 degrees Horizontal)
- Image Adjustment Features: Color Management, Auto Picture Control, Gamma Adjustment
- 10 bit Digital Processing for Smoother Gradations and Color Reproductions
- Progressive Scanning (480i, 575i, 1080i) with 2:3 / 2:2 Pull Down Response (480i)
- Customize Logo Display with Lock Function
- DVI-D (RGB Digital) Terminal, HDCP Compatible
- VGA (RGB Analog) Input/Output
- Other Input Terminals: 5 BNC, Component, S-Video, Composite
- Quiet Operation: 36dB (Quiet Mode)
- Size (W x D x H): 12.6 x 16.9 x 6.6 in. (319 x 430 x 168mm)
- 3 Year Parts and Labor Warranty -120 Day Lamp Life Warranty

- Projector Wireless/Wired Remote Control (AAA-size Batteries Included)
- VGA Computer Cable Wired Remote Cable
- Mouse Control Cable (USB) Lens Cap User's Manual
- Warranty Card

^{*} See back cover for details on the "Triple P" Program.



OPTIONAL PROJECTOR LENSES FOR THE LV-7575



Ultra Wide-Angle Lens LV-IL01

- Lens: f=22.33mm, F2.5
- Throw Distance: 3.7 to 6.4 ft. (1.13 to 1.96m)
- Projected Image Size: 70 to 120 in.
- Throw Ratio: 0.8:1 (D:W)



Wide-Angle Zoom Lens LV-IL02

- Lens: f=34.33 to 48.02mm,
 F2.5 to 3.06, 1.4x zoom
- Throw Distance: 3.2 to 25.4 ft.(0.98 to 7.74m)
- Projected Image Size: 40 to 300 in.
- Throw Ratio: 1.25 to 1.8:1 (D:W)



Long Focus Zoom Lens LV-IL03

- Lens: f=63.5 to 111.5mm,
 F2.03 to 2.89, 1.8x zoom
- Throw Distance: 8.9 to 46.7 ft. (2.73 to 14.23m)
- Projected Image Size: 60 to 300 in.
- Throw Ratio: 2.29 to 4.17:1 (D:W)



Ultra Long Focus Zoom Lens LV-IL04

- Lens: f=111.6 to 155.2mm, F2.06 to 2.73, 1.4x zoom
- Throw Distance: 11.4 to 82.0 ft. (3.48 to 25.0m)
- Projected Image Size: 40 to 300 in.
- Throw Ratio: 4.15 to 5.78:1 (D:W)

Lens changes must be performed by an authorized Canon representative.









6.8 LBS. (3.1KG)

FEATURES

- Native XGA Resolution, Projects UXGA and SXGA (compressed)
- 2500 ANSI Lumens (85% Uniformity)
- · Quick Start (8 seconds) and Quick Cooling (30 seconds)
- 600:1 Contrast Ratio
- Lens: f=17.7 to 28.3mm, F1.6 to 2.5, 1.6x zoom
- 100-in. Screen: 9.2 to 14.3 ft. (2.8 to 4.3m)
- Throw Distance: 3.5 to 27.7 ft. (1.1 to 8.4m)
- Projected Image Size: 25 to 300 in.
- Throw Ratio: 1.37 to 2.14:1 (D:W)
- Automatic and Manual Keystone Correction (±30 degrees vertical)
- DVI Input for connection to devices with digital output
- Enhanced Wall Color Correction
- Color Management System for accurate and precise image adjustment
- 1 VGA + DVI to VGA Adapter (included)
- Component Video Input (with optional adapter cable)
- Connects with HDTV, DVD player, VCR, digital camcorder or document camera
- User-Friendly On-Screen Menu, Automatic Power Off Timer
- Flexible Image Settings preset image modes designed to help bring out the best image quality
- Wireless Mouse Control (includes Drag & Drop feature)
- Long Life Lamp: up to 3000 hours in Quiet Mode
- Quiet Operation: 29dB (Quiet Mode)
- Size (W x D x H) 12.2 x 10.4 x 4.3 in. (310 x 265 x 109mm)
- 3-Year Parts and Labor Warranty 120-Day Lamp Life Warranty

- Projector Wireless Remote Control (AAA-size batteries included)
- Remote Mouse Receiver
 DVI to VGA Adapter
 Power Cable
- VGA Computer Cable
 Lens Cap
 Soft Carrying Case
 CD-ROM
- · Warranty Card

^{*} See back cover for details on the "Triple P" program.









6.6 LBS. (3.0KG)

FEATURES

- Native XGA Resolution, Projects UXGA and SXGA (compressed)
- 2000 ANSI Lumens (85% Uniformity)
- Quick Start (8 seconds) and Quick Cooling (30 seconds)
- 600:1 Contrast Ratio
- Lens: f=17.7 to 28.3mm, F1.6 to 2.5, 1.6x zoom
- 100-in. Screen: 9.6 to 15.1 ft. (2.9 to 4.6m)
- Throw Distance: 3.7 to 29.1 ft. (1.1 to 8.8m)
- Projected Image Size: 25 to 300 in.
- Throw Ratio: 1.44 to 2.25:1 (D:W)
- Manual Keystone Correction (±30 degrees vertical)
- Enhanced Wall Color Correction
- Color Management System for accurate and precise image adjustment
- 1 VGA Input (connect two laptops at the same time), 1 VGA Output
- Component Video Input (with optional adapter cable)
- Connects with HDTV, DVD player, VCR, digital camcorder or document camera
- User-Friendly On-Screen Menu, Automatic Power Off Timer
- Flexible Image Settings preset image modes designed to help bring out the best image quality
- . Long Life Lamp: up to 3000 hours in Quiet Mode
- Quiet Operation: 29 dB (Quiet Mode)
- Wireless Mouse Control (includes Drag & Drop feature)
- Size (W x D x H): 12.2 x 10.4 x 4.3 in. (310 x 265 x 109mm)
- 3-Year Parts and Labor Warranty 120-Day Lamp Life Warranty

- Projector
 Wireless Remote Control (AAA-size batteries included)
- Remote Mouse Receiver
 Power Cable
 VGA Computer Cable
- Lens Cap
 Soft Carrying Case
 Carrying Handle
- Quick-Start Guide
 Warranty Card

^{*} See back cover for details on the "Triple P" program.

V-X7









6.4 LBS. (2.9KG)

FFATURES

- Native XGA Resolution, Projects UXGA and SXGA (compressed)
- 1500 ANSI Lumens (85% Uniformity)
- Quick Start (8 seconds) and Quick Cooling (30 seconds)
- 500:1 Contrast Ratio
- Lens: f=17.7 to 28.3mm, F1.6 to 2.5, 1.6x zoom
- 100-in. Screen: 9.6 to 15.1 ft. (2.9 to 4.6m)
- Throw Distance: 3.7 to 29.1 ft. (1.1 to 8.8m)
- Projected Image Size: 25 to 300 in.
- Throw Ratio: 1.44 to 2.25:1 (D:W) Enhanced Wall Color Correction
- Manual Keystone Correction (±30 degrees vertical)
- Color Management System for accurate and precise image adjustment
- 1 VGA Input, 1 VGA Output
- Component Video Input (with optional adapter cable)
- · Connects with HDTV, DVD player, VCR, digital camcorder or document camera
- User-Friendly On-Screen Menu, Automatic Power Off Timer
- Flexible Image Settings preset image modes designed to help bring out the best image quality
- Long Life Lamp: up to 4000 hours in Quiet Mode
- · Quiet Operation: 25 dB (Quiet Mode)
- Size (W x D x H): 12.2 x 10.4 x 4.3 in. (310 x 265 x 109mm)
- 3-Year Parts and Labor Warranty 120-Day Lamp Life Warranty

- Projector
 Wireless Remote Control (AAA-size batteries included)
- Power Cable
 VGA Computer Cable
 Lens Cap
- Soft Carrying Case Quick-Start Guide Warranty Card

^{*} See back cover for details on the "Triple P" program.

CANON TECHNOLOGY

BENEFIT FROM OUR OPTICAL EXPERIENCE

The heart of any projector is its optics. Nearly 70 years of expertise in designing and crafting precision lenses for photography, broadcast TV cameras and camcorders goes into every lens we manufacture. Our projector lenses deliver remarkably broad zoom ranges and incredibly short throw distances and consistently produce images with superior color and clarity.

CANON THROW DISTANCE CHART

LV-7575 (Standard Lens)

Projection Image Size		31"	40"	100"	200"	300"	400"
Projection	Wide	4.6'	4.6'	11.8'	23.9'	36.0'	48.2
Distance	Tele	4.6'	5.9'	15.4'	31.5'	47.2'	48.2

LV-7265

Projection Image Size		25"	40"	100"	150"	200"	300"
Projection	Wide		3.6'	9.2'	13.8'	18.4'	27.7'
Distance	Tele	3.5'	5.7'	14.3'	21.6'	-	_

LV-7260/LV-X7

Projection Image Size		25"	40"	100"	150"	200"	300"
Projection	Wide	_	3.8'	9.6'	14.5'	19.4'	29.1
Distance	Tele	3.7'	5.9'	15.1'	22.7	7—1	_

^{*} For more detailed throw distance information, please visit us at www.canonprojectors.com

MAXIMUM IMPACT IN MINIMUM SPACES

Normally, a projector must be positioned far away from a screen to project a large image. This is not the case with Canon projectors. They feature wide-angle zoom lenses, allowing you to achieve big, vibrant images from as little as 9.2 feet (2.8m), making them ideal for a small conference room.



OPTIONAL ACCESSORIES

FOR IV-7575

Network Imager LV-NI02

The Network Imager LV-NI02 connects the LV-7575 to your computer network, enabling remote management of the projector through



a simple browser-based graphic user interface. This makes a number of tasks easier, such as programming for operation on a daily or weekly schedule, input mode switching and picture adjustment.

Send status alerts via email, furthermore, it offers remote transfer of images, and centralized control of multiple projectors.

Replacement Lamp LV-LP28 Ceiling Mount Adapter LV-CL07 DVI Cable LV-CA29

For IV-7265



Replacement Lamp LV-LP26



Ceiling Mount Adapter LV-CL11



Component Video Adapter LV-CA32



RS-232C Cable LV-CA34

For LV-7260



Replacement Lamp LV-LP26



Ceiling Mount Adapter LV-CL11



Component Video Adapter LV-CA32



RS-232C Cable LV-CA34

For LV-X7



Replacement Lamp LV-LP27



Ceiling Mount Adapter LV-CL11



Component Video Adapter LV-CA32



RS-232C Cable LV-CA34

RE-455X



20.7 LBS. (9.4KG)

FEATURES

- Display paper documents and 3-D objects
- XGA Resolution (1024 x 768)
- Superior Canon Optics: 12x Optical Power Zoom Lens
- Connects easily to your projector, computer monitor, TV, VCR or DVD recorder
- Convenient Front Panel Controls
- White Paper Mode enhances the appearance of text documents
- Zoom Preset automatically zooms to cover an 8-1/2 x 11 in. document
- Image Freeze
- Auto and Manual Focusing, Exposure and White Balance
- One Shot Auto Focus ideal when switching objects frequently
- Adjustable Twin Fluorescent Lamps provides uniform lighting
- VGA Input/Output
- S-Video and Composite Output
- Foldable Design for Excellent Portability
- Size (W x D x H): In Use: 28.4 x 20.7 x 21.9 in.

(722 x 525 x 556mm)

Folded: 19.1 x 20.7 x 7.2 in.

(486 x 525 x183mm)

• 1-Year Parts and Labor Warranty

- Visualizer
 VGA Cable
 AC Cable
 Dust Cover
- User's Manual Warranty Card

TRIPLE P PROGRAM



Canon's Projector Protection Program, also known as "Triple P", is a service program that provides a loaner projector of equal or greater quality in the event that your projector needs to be repaired.

- Free to any buyer within their first year of new product warranty
- Canon Customer Support Center toll free hotline: 1-800-828-4040
- Customer Service Hours: 8 a.m. to Midnight, Monday to Friday
 10 a.m. to 8 p.m., Saturday
- For next business day delivery of loaner projectors, Customer Activation Form must be received by Canon Customer Support Center by 3 p.m. EST (Monday to Friday)
- Customer must provide a valid credit card as security for the loaner unit
- Delivery not available on Saturday and Sunday
- Program available for products purchased and utilized in the U.S.A. only
- · Applies to Canon SXGA+ and XGA resolution products only
- Loaner unit based on availability
- Program subject to change at any time without any given notice

Errors and omissions excepted. Specifications are subject to change without notice.



1-800-OK-CANON www.usa.canon.com

Canon U.S.A., Inc. One Canon Plaza Lake Success, NY 11042 U.S.A.

Canon Canada Inc. 6390 Dixie Road Mississauga, Ontario L5T 1P7 Canada

Canon Latin America 703 Waterford Way, Suite 400 Miami, FL 33126 U.S.A.

Canon Mexicana, S. de R.L. de C.V. Blvd. Manuel Ávila Camacho No. 138, Piso 17 Col. Lomas de Chapultepec C.P. 11000 México, D.F. México