Everything should be this easy VT595 and VT695 digital projectors.



LONG LAMP LIFE

EASY TO USE

AUTOSENSE TECHNOLOGY

MONITOR OUTPUT

COLOR MANAGEMENT

AUTOMATIC KEYSTONE CORRECTION

5-WATT SPEAKER

DVI-I INPUT

VARIABLE AUDIO OUT

Easy to use and at the right price, the VT Series projectors provide all the essential features that you need to connect with your audience.

ESSENTIAL FEATURES FOR EASE OF USE.

- Plug and play intuitive setup and operation.
- Quick start up lets you begin presenting in seconds.
- **Bright images** easily viewed in any application.
- Versatile color-coded connections to computer, video sources and external monitor.
- Lightweight design for easy transport.
- Automatic keystone correction SquareShotTM technology instantly projects a square image even when the projector is set up at a steep offset angle to the screen.
- **Autosense**TM intuitively syncs the projector with most computer signals and features onetouch image optimization.
- One touch source changes and complete menu control using the intuitive projector keypad.

VERSATILE FEATURES AND POWERFUL PERFORMANCE.

- With XGA native resolution, high brightness up to 2500 lumens and patented NEC technologies like Advanced AccuBlend[™] and VORTEX[™] Technology, the VT Series displays impressive image quality.
- Vertical position of the image can be adjusted when the **Cinema aspect (wide screen) ratio** is in use.
- **Built-in wall color correction presets** provide for adaptive color tone correction to display properly on non-white surfaces.
- Focus in on details with **up to 400% image magnification.**
- **Easy remote** allows you to adjust lamp mode, aspect ratio, volume and image all with the touch of a button.
- Optional IR receiver can be connected to computer for remote mouse control.
- **Variable audio-out** enables remote control to be used to adjust volume of self-powered external speakers that are connected to the projector.
- Powerful 5-watt speaker provides volume needed for large rooms.
- Dual computer inputs, including one DVI-I, ensures quick switching between presentations.

SAVE MONEY, RESOURCES AND YOUR PROJECTOR.

- The VT Series projectors are extremely affordable.
- Extended lamp life with Eco-modeTM technology that increases lamp life up to 3,000 hours.
- $\circ~$ Nearly silent operation with noise level as low as 29dB
- Automatic timer can be set to shut off the projector at selected time intervals.
- **Power management** enables projector to automatically turn off when an incoming signal is not detected from any of the inputs.
- Password protection restricts unauthorized use of projector
- **Cabinet control lock setting** enables user to deactivate buttons on cabinet to prevent unwanted changes to projector settings.

Because It's your Image





LINIOUE FEATURES

ONIQUEILATOR	LJ
Advanced AccuBlend	Ensures detailed images when non-native resolution
	sources are connected to the projector.
Autosense	Automatically syncs with any computer signal and
	features one touch image optimization.
VORTEX™ Technology Plus	Breakthrough image processing technology improves
	white level, color accuracy, dynamic range and varying
	levels of black in an image.
Eco-Mode™ Technology	Extends lamp life, lowers audible noise and reduces total
	cost of ownership.
Built-in Wall Color Correction	Presets provide for adaptive color tone correction to
	display properly on non-white surfaces.
Image Magnification	64-step image magnification with location control.
Sleep Timer	Count down timer can be set to automatically turn off
	the projector.
5-Watt Speaker	Provides volume needed for larger rooms
WARRANTY	

Registered owers receive a 3-year limited warranty including InstaCare. Includes three covered for one year or 500 hours - whatever comes first. InstaCare provides the original owner one year of either limited 3 business day repair/return or next business day exchange. year limited warranty on parts and one year limited warranty on labor. The lamp is

IN THE BOX

Carrying case, carrying handle for projector, remote control, battleries, power cord, RGB signal cable, lens cap, user's manual on CD-ROM, quick start guide, product registration card, DVI-I – VGA adapter



For more information, call 1.800.NEC.INFO or visit www.necvisualsystems.com

NEC is a registered trademark of NEC Corporation. All other trademarks are the property of their respective owners. All specifications subject to change without notice.

NEC Corporation of America Visual Systems Division 1250 Arlington Heights Rd., Suite 400 Itasca, IL 60143-1248

Everything should be this easy VT595 and VT695 digital projectors.

OPTI	CAL
------	-----

OPTICAL			
Display Technology	0.6" LCD		
Resolution	Native:	XGA 1024 x 768	
Light Output (lumens)	Maximum: VT595	UXGA 1600 x 1200 2000 normal / 1600 eco	
Light Output (lumens)	VT695	2500 normal / 1900 eco	
Contrast Ratio	600:1	2500 Holman 1500 CC0	
Lamp Type	VT595	190W DC/150W eco	
	VT695	200W DC/150W eco	
Lamp Life (up to)		nal / 3000 hours eco	
Screen Size (diagonal)	21 - 300 in, .53	-/.6 M	
Throw Ratio Projection Distance	1.5 – 1.8 2.3 to 36.4 ft, .7	7 to 11 1 m	
Projection Angle		9.9 – 10.3° wide	
Lens	Zoom	1.0 to 1.2	
	Focus	Manual	
	F-#, f-#	F=1.7 to 2.07 mm, f=18.9 to 22.7mm	
Keystone Correction	Automatic or ma	anual +/- 30°	
SIGNAL COMI	PATIBILITY/	CONNECTIVITY	
Scan Rate	Horizontal	15 to 100 kHz	
	Vertical	50 to 120 Hz	
Supported Video	NTSC, NTSC4.43	3, PAL, PAL-60, PAL-M, PAL-N, SECAM	
Standards	1000: 700- 57	Ca. E7Ci. 480a. 480i V/Ch/Cr. component (with entired adapter. ADD. CV/1E)	
SD/HD Video Signal Compatibility	10801, 720p, 57	6p, 576i, 480p, 480i,Y/Cb/Cr component (with optional adapter – ADP-CV1E)	
PC Signal Compatibility	VGA SVGA XG	A, SXGA, SXGA+, UXGA	
Macintosh Compatibility	Yes		
Input/Output Terminals	RGB 1 (analog)		
	RGB2	DVI-I (digital and analog)	
	Video 1 Video 2	RCA S-Video	
	Audio 1	L/R RCA (shared by video sources)	
	Audio 2	1/8 inch stereo (shared by computer inputs)	
	Audio Out	Variable audio out	
	Monitor Out	Yes	
Audio	5-Watt speaker		
External Control Sync Compatibility	RS232, IR	Composite Sync / Sync on G	
	Separate Sync /		
ELECTRICAL			
Power Req.	100 - 240VAC, !	50 / 60Hz	
Input Current	3.1 / 1.3A		
Power Consumption	270W / 220W (\	/T595), 280W / 215W (VT695)	
MECHANICAL	_		
Installation Orientation	-	or / Rear, Ceiling / Front, Ceiling / Rear	
Dimensions (WxDxH)		I.4 in, 309 x 258 x 112 mm	
Net Weight	6.4 lbs, 2.9 kg		
Fan Noise	35 dB normal / 2		
Regulations	USA UL 1950 FC	C Class B, Canada CSA950 (C-UL)	
ENVIRONMEN	ITAL		
Operational Temp	41° to 95°F / 5°	to 40°C	
Humidity	20-80% non-co		
Storage	14° to 122°F / -		
		NTY PROGRAMS	
Accessories			
IR-RCVR	IR receiver enabl	es PJ remote to control PC and MAC functions	
WPA001	802.11b/g wirel		
SPKR30	Amplified 30 wa		
SC200	Security cable attaches to projector lock slot		
ADP-CV1E	Component vide	eo to VGA adapter	
	Loothor coco	h compartments for lanton and projector	
LEATHERCASE LEATHERROLLER		h compartments for laptop and projector ase for laptop and PJ, fits in most airplane storage bins	
VT70ATA		plastic shipping case for projector	
Installation			
VL80CM		vith adapter plate designed for VT90 Series projectors	
NP01UCM		mount for projectors weighing less than 40 pounds	
ADJ006009		stable extension column for use with projector mount	
ADJ0012018 ADJ0203	12 to 18 inch adjustable extension column for use with projector mount		
ADJ0203 ADJ0305	2 to 3 foot adjustable extension column for use with projector mount 3 to 5 foot adjustable extension column for use with projector mount		
SCP100		ended ceiling plate for use with ceiling mount	
Replacement Parts		<u> </u>	
VT80LP	Replacement lan		
VT85LP		np for VT490, VT590, VT595, VT695	
RMT-PJ21	Replacement remote control		
PWRCRD-VT70	Replacement po		
RGBCBL-PJPX Warranty Programs	Replacement RG	וט זוקוומו כמטול	
VLNPL-01	Extends term of	parts and labor warranty to include 3 years labor	
VLIC03		InstaCare service program to 3 years	
VLMTC-02	3 year internation	nal service program	
	D 1 I	ng program, disposal certificate	
NECECO			
NECECO VTP04	Extends term of	VT90 Series parts warranty to 4 years	
NECECO	Extends term of		

NEC