

## NEC VT700



- Native resolution: 1,024 x 768
- Max. resolution: 1,600 x 1,200
- Brightness: 3,000 ANSI Lumens
- Whisper quiet: 29 dB (A)\*
- Quick-Start-/Quick-Power-Off function
- Automatic, vertical Keystone Correction
- Manual wall colour correction
- Off-timer function
- Short throw lens
- 3,000 hrs lamp life\*
- 3 years warranty\*\*

**see more.**

NEC Display Solutions

# NEC VT700

Article No.:	60002040
Display:	3 x 1.6 cm (0.63") p-Si with MLA LCD-Panel
Lamp:	210 W AC (172 W AC Eco Mode)
Lamp Life:	2,000 hrs (3,000 hrs Eco Mode)
Brightness:	3,000 ANSI Lumens (2,400 ANSI Lumens Eco Mode)
Contrast:	500:1
Lens:	F= 1.7–2.07, f= 18.9–22.7 mm
Minimum Diagonal:	53 cm
Maximum Diagonal:	762 cm
Projection Distance:	0.7–11.1 m
Projection Factor:	1.5–1.8:1
Frequency:	Horizontal: 15–100 kHz (RGB: 24–100 kHz), vertical: 50–120 Hz
Native Resolution:	1,024 x 768 (XGA)
Supported Resolutions:	1,600 x 1,200 (UXGA), 1,920 x 1,080 (HDTV 1,080i/60, HDTV 1,080i/50), 1,280 x 720 (HDTV 720p), 1,280 x 1,024 (SXGA), 1,280 x 1,024 (Mac 23"), 1,152 x 870 (Mac 21") compressed, 1,024 x 768 (XGA), 800 x 600 (SVGA), 832 x 624 (Mac 16"), 640 x 480 (VGA/Mac 13"), 720 x 480 (SDTV 480p), 720 x 480 (DVD progressive), 720 x 576 (DVD progressive)
<b>INPUT/OUTPUT TERMINAL:</b>	
Computer Analog	1 x input: Mini D-SUB 15-pin, compatible to component (YPbPr) 1 x output: Mini D-SUB 15-pin
DVI	1 x input: DVI-I with HDCP, shared with DVI analog ( DVI-VGA adapter)
Video	1 x input: Phono jack
S-Video	1 x input: mini DIN 4-pin (Hoseiden Connection)
Audio	1 x input: 3.5 mm stereo mini jack (Computer analog and digital) 1 x input: stereo jack (Video and S-Video) 1 x output: 3.5 mm stereo mini jack (variable)
PC-Control (RS-232)	1 x input: mini DIN 8-pin (female)
Video Signals:	PAL/PAL60/NTSC/SECAM/NTSC 4.43/PAL-N/PAL-M
Audio Functions:	5 W mono speaker
Zoom:	Manual
Focus:	Manual
Benefits:	Automatic and manual vertical Keystone Correction (V= ±30°), manual wall colour correction, colour management, RS-232 control, Quick-Start /Quick-Power-Off function, Off-timer function, source select with beep function, short throw lens, help function, Plug&Play, password security function, OSD with 21 languages, optional user Logo
Remote Control (RD-427E):	Source select, Power (On-OFF), Page (up, down), Select (up,down,left,right), picture mute function, picture adjust, aspect ratio, optional presentation and Mouse control, auto adjust, freeze function, magnify, audio control, lamp mode, Help
Dimensions (W x H x D):	309 x 112 x 258 mm (without lens and feet)
Weight:	3.1 kg
Power Supply:	100–240 V AC/50–60 Hz
Power Consumption:	295 W max./Stand-by Mode 9 W
Fan Noise:	29 dB (A)*
Safety/Ergonomics:	CE, TÜV GS
Warranty:	Projector: 3 years pan-European premium service Lamp: 6 months, max. 1,000 hrs**
Shipping Contents:	Projector, IR remote control (RD-427E), Mini D-SUB signal cable, power cord (4.5 m), lens cap, users manual on CD-ROM, quick setup guide, soft case, handle, DVI-VGA adapter
Optional Accessories:	NPO5LP (lamp), NPO3CM (ceiling mount kit), NPO1MR (mouse receiver)

\* Eco Mode

\*\* please refer to our warranty conditions under: [www.nec-display-solutions.com](http://www.nec-display-solutions.com)

All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. JUNE 2007

see more.

NEC Display Solutions

[www.nec-display-solutions.com](http://www.nec-display-solutions.com)  
NEC Display Solutions Europe GmbH

VT700-UK/6/07